

General Instructions

According to MS 123B.571, radon testing conducted in public school buildings eligible for health and safety (i.e., not charter schools) must be reported to the Minnesota Department of Health.

For the purpose of this form, a building is defined as an occupied facility that has a unique address, including administrative buildings. A building could be a single structure or a complex of structures. For reference, all district owned buildings entered on the Minnesota Department of Education "Facilities Age and Square Footage Report" should be utilized.

- 1. Submit summary information and raw data if either of the following apply:
 - a. Radon testing has been completed in a building since the MDH 'School Radon Testing Survey' dated April 4, 2011, or
 - b. Radon testing was completed at some time previously and your district did not report radon testing in the MDH 'School Radon Testing Survey' dated April 4, 2011.
- 2. Complete one survey for each building tested
- 3. Submit the survey, raw data (e.g., laboratory analysis report) and a building map to MDH by email, to health.indoorair@state.mn.us
- 4. If follow-up testing, mitigation, and/or post-mitigation testing is not yet completed, please submit a completed form and raw data when the work is completed.

Contact	t Person for this Form	
Name:_	Kain Smith	
Phone:_	952-496-5046	
Email: _	KrSmith@Shakopee. KIZ. mn. us	
Mailing	Address: 1200 Shakoper Town Source Shakoper 19145.	5379

Radon Results for Each School Building			
1. District Name & Number: Shakopee Public Schools #720			
2. School Building Name: Central Family Center			
3. School Building Address: 505 Holones St. S.			
4. What type of test kit was used? Manufacturer: Landauer Device name: RadtraK 2			
Comments			
5. When were the test kits retrieved? 3			
Comments			
6. How long were the test kits deployed in the rooms?			
Comments:			
7. Was testing conducted over: a. Weekends? Yes X No b. Holidays or Breaks? Yes X No			
Comments:			
8. Were all frequently-occupied rooms in contact with the ground tested? Yes No _X This includes: 1) rooms on grade and; 2) rooms above unoccupied spaces that are in contact with the ground, such as rooms above storage rooms, crawl spaces, tunnels, and boiler rooms. If only a sample or portion of rooms were tested, then respond with 'no'.			
Comments: 3 detectors were missing			
9. How many frequently-occupied rooms were tested?			
Comments: 3 missing only 15 results			
10. How many frequently-occupied rooms were at or above four picocuries per liter (≥ 4 pCi/L)?			
Comments:			
11. Were test results reported at a school board meeting? Yes X No If results will be reported at the next meeting, note in comments the month and year of the scheduled meeting in the comments section.			
Comments:			

12. How many of the rooms ≥ 4 pC/L had follow-up testing results that were:
a. ≥ 4 pCi/L b. ≤ 4 pCi/L c. not tested
'Follow-up' testing means testing done, prior to any radon mitigation, to confirm or verify initial test results in those
rooms ≥ 4 pCi/L are, in fact, ≥ 4 pCi/L. If a continuous radon monitor (CRM) was used, indicate concentration during
occupied times. If no follow-up testing was done, write the number of rooms not tested. If follow-up testing will be
done in the future, note in comments the planned month and year in the comments section.
Comments:
10 Tr
13. How many of the rooms ≥ 4 pCi/L:
a. were mitigated? b. had other corrective measures? 'Mitigated' means building changes such as adjusting the existing HVAC system, increasing fresh air ventilation rate,
'Mitigated' means building changes such as adjusting the existing HVAC system, increasing fresh air ventilation rate,
balancing air flow to rooms, or other such modifications. 'Other corrective measures' could include moving staff out of
a room and making a room unoccupied or trying to seal radon entry points. If mitigation or other corrective measure(s) will be completed in the future, note in comments the planned month and year in the comments section.
with be completed in the future, note in comments the planned month and year in the comments section.
Comments:
14. How many rooms re-tested after mitigation were:
a. $\geq 4 \text{ pCi/L}$ b. $< 4 \text{ pCi/L}$ c. not tested
If post-mitigation re-testing will be completed in the future, note the planned month and year in the comments section.
Comments:



General Instructions

Contact Person for this Form

According to MS 123B.571, radon testing conducted in public school buildings eligible for health and safety (i.e., not charter schools) must be reported to the Minnesota Department of Health.

For the purpose of this form, a building is defined as an occupied facility that has a unique address, including administrative buildings. A building could be a single structure or a complex of structures. For reference, all district owned buildings entered on the Minnesota Department of Education "Facilities Age and Square Footage Report" should be utilized.

- 1. Submit summary information and raw data if either of the following apply:
 - a. Radon testing has been completed in a building since the MDH 'School Radon Testing Survey' dated April 4, 2011, or
 - b. Radon testing was completed at some time previously and your district did not report radon testing in the MDH 'School Radon Testing Survey' dated April 4, 2011.
- 2. Complete one survey for each building tested
- 3. Submit the survey, raw data (e.g., laboratory analysis report) and a building map to MDH by email, to health.indoorair@state.mn.us
- 4. If follow-up testing, mitigation, and/or post-mitigation testing is not yet completed, please submit a completed form and raw data when the work is completed.

Name:_	Kain Smith	
	952-496.5046	
Email: _	KrSmith@Shakopee. K12.mn.us	
Mailing .	Address: 1200 Shatopee Town Sauce	Shakare 171V 55379

Radon Results for Each School Building
1. District Name & Number: Shakopee Public Schools #720
2. School Building Name: District Office
3. School Building Address: 1200 Shakopee Town Square
4. What type of test kit was used? Manufacturer: Landover Device name: Rad frak Z
Comments
5. When were the test kits retrieved?
Comments
6. How long were the test kits deployed in the rooms?
Comments:
7. Was testing conducted over: a. Weekends? Yes X No b. Holidays or Breaks? Yes X No
Comments:
8. Were all frequently-occupied rooms in contact with the ground tested? YesNoX
Comments: 2 defectors missing
9. How many frequently-occupied rooms were tested?
Comments: 2 missing so only 18 results
10. How many frequently-occupied rooms were at or above four picocuries per liter (≥ 4 pCi/L)?
Comments:
11. Were test results reported at a school board meeting? Yes No If results will be reported at the next meeting, note in comments the month and year of the scheduled meeting in the comments section.
Comments:

12. How many of the rooms ≥ 4 pC/L had follow-up testing results that were:
a. $\geq 4 \text{ pCi/L}$ b. $< 4 \text{ pCi/L}$ c. not tested
'Follow-up' testing means testing done, prior to any radon mitigation, to confirm or verify initial test results in those rooms ≥ 4 pCi/L are, in fact, ≥ 4 pCi/L. If a continuous radon monitor (CRM) was used, indicate concentration during occupied times. If no follow-up testing was done, write the number of rooms not tested. If follow-up testing will be done in the future, note in comments the planned month and year in the comments section.
Comments:
13. How many of the rooms ≥ 4 pCi/L: a. were mitigated? b. had other corrective measures? 'Mitigated' means building changes such as adjusting the existing HVAC system, increasing fresh air ventilation rate, balancing air flow to rooms, or other such modifications. 'Other corrective measures' could include moving staff out o a room and making a room unoccupied or trying to seal radon entry points. If mitigation or other corrective measure(s) will be completed in the future, note in comments the planned month and year in the comments section.
Comments:
14. How many rooms re-tested after mitigation were: a. ≥ 4 pCi/L b. ≤ 4 pCi/L c. not tested If post-mitigation re-testing will be completed in the future, note the planned month and year in the comments section.
Comments:



General Instructions

According to MS 123B.571, radon testing conducted in public school buildings eligible for health and safety (i.e., not charter schools) must be reported to the Minnesota Department of Health.

For the purpose of this form, a building is defined as an occupied facility that has a unique address, including administrative buildings. A building could be a single structure or a complex of structures. For reference, all district owned buildings entered on the Minnesota Department of Education "Facilities Age and Square Footage Report" should be utilized.

- 1. Submit summary information and raw data if either of the following apply:
 - a. Radon testing has been completed in a building since the MDH 'School Radon Testing Survey' dated April 4, 2011, or
 - b. Radon testing was completed at some time previously and your district did not report radon testing in the MDH 'School Radon Testing Survey' dated April 4, 2011.
- 2. Complete one survey for each building tested
- 3. Submit the survey, raw data (e.g., laboratory analysis report) and a building map to MDH by email, to health.indoorair@state.mn.us
- 4. If follow-up testing, mitigation, and/or post-mitigation testing is not yet completed, please submit a completed form and raw data when the work is completed.

Contact	Dorgon	for this	Laura
Cuntact	I CI SUII	101 UIIS	rorm

Name:_	Kain Smith	
Phone:_	952-496.5046	
Email: _	KrSmith@Shakopee. KIZ. Mn. US	
Mailing	Address: 1200 Shatopee Town Square	Shakopec, MV 55379

Radon Results for Each School Building			
1. District Name & Number: Shakopee Public Schools #720			
2. School Building Name: <u>Fagle Creek Elementary</u>			
3. School Building Address: 6855 Woodward Ave			
4. What type of test kit was used? Manufacturer: Landauer Device name: Radtra K 2			
Comments			
5. When were the test kits retrieved? 3/17 (month/year) More than one date can be entered if parts of buildings were tested at different times			
Comments			
6. How long were the test kits deployed in the rooms?			
Comments:			
7. Was testing conducted over: a. Weekends? Yes X No b. Holidays or Breaks? Yes X No No			
Comments:			
8. Were all frequently-occupied rooms in contact with the ground tested? Yes No X This includes: 1) rooms on grade and; 2) rooms above unoccupied spaces that are in contact with the ground, such as rooms above storage rooms, crawl spaces, tunnels, and boiler rooms. If only a sample or portion of rooms were tested, then respond with 'no'.			
Comments: 6 missing defectors			
9. How many frequently-occupied rooms were tested? 33			
Comments: 6 missing so only 27 results			
10. How many frequently-occupied rooms were at or above four picocuries per liter (≥ 4 pCi/L)? 13			
Comments:			
11. Were test results reported at a school board meeting? Yes X No			
Comments:			

12. How many of the rooms ≥ 4 pC/L had follow-up testing results that were: a. ≥ 4 pCi/L b. < 4 pCi/L c. not tested 'Follow-up' testing means testing done, prior to any radon mitigation, to confirm or verify initial test results in those rooms ≥ 4 pCi/L are, in fact, ≥ 4 pCi/L. If a continuous radon monitor (CRM) was used, indicate concentration during occupied times. If no follow-up testing was done, write the number of rooms not tested. If follow-up testing will be done in the future, note in comments the planned month and year in the comments section.
Comments: Roon 119 was missed on the follow up testing
13. How many of the rooms ≥ 4 pCi/L: a. were mitigated? b. had other corrective measures? 'Mitigated' means building changes such as adjusting the existing HVAC system, increasing fresh air ventilation rate, balancing air flow to rooms, or other such modifications. 'Other corrective measures' could include moving staff out o a room and making a room unoccupied or trying to seal radon entry points. If mitigation or other corrective measure(s) will be completed in the future, note in comments the planned month and year in the comments section.
Comments:
14. How many rooms re-tested after mitigation were: a. ≥ 4 pCi/L b. < 4 pCi/L c. not tested If post-mitigation re-testing will be completed in the future, note the planned month and year in the comments section. Comments:

. .

.

4



General Instructions

According to MS 123B.571, radon testing conducted in public school buildings eligible for health and safety (i.e., not charter schools) must be reported to the Minnesota Department of Health.

For the purpose of this form, a building is defined as an occupied facility that has a unique address, including administrative buildings. A building could be a single structure or a complex of structures. For reference, all district owned buildings entered on the Minnesota Department of Education "Facilities Age and Square Footage Report" should be utilized.

- 1. Submit summary information and raw data if either of the following apply:
 - a. Radon testing has been completed in a building since the MDH 'School Radon Testing Survey' dated April 4, 2011, or
 - b. Radon testing was completed at some time previously and your district did not report radon testing in the MDH 'School Radon Testing Survey' dated April 4, 2011.
- 2. Complete one survey for each building tested
- 3. Submit the survey, raw data (e.g., laboratory analysis report) and a building map to MDH by email, to health.indoorair@state.mn.us
- 4. If follow-up testing, mitigation, and/or post-mitigation testing is not yet completed, please submit a completed form and raw data when the work is completed.

Contact	Person	for this	Form
---------	--------	----------	------

Name:_	Kain Smith	
Phone:_	952-496-5046	
Email: _	KrSmith@Shakopee. KIZ. mn. us	
Mailing	Address: 1200 Shakopee Town Square	Shatopec, MV 55379

Radon Results for Each School Building
1. District Name & Number: Shakopee Public Schools #720
2. School Building Name: Jackson Elementary
3. School Building Address: 1601 Lusitano St.
4. What type of test kit was used? Manufacturer: Land auer Device name: Rad tra K Z
Comments
5. When were the test kits retrieved?
Comments_
6. How long were the test kits deployed in the rooms?
Comments:
7. Was testing conducted over: a. Weekends? Yes X No b. Holidays or Breaks? Yes X No
Comments:
8. Were all frequently-occupied rooms in contact with the ground tested? Yes No _X This includes: 1) rooms on grade and; 2) rooms above unoccupied spaces that are in contact with the ground, such as rooms above storage rooms, crawl spaces, tunnels, and boiler rooms. If only a sample or portion of rooms were tested, then respond with 'no'.
Comments: 4 missing detectors
9. How many frequently-occupied rooms were tested?
Comments: 4 missing so only 29 results
10. How many frequently-occupied rooms were at or above four picocuries per liter (≥ 4 pCi/L)?
Comments:
11. Were test results reported at a school board meeting? Yes No If results will be reported at the next meeting, note in comments the month and year of the scheduled meeting in the comments section.
Comments:

12. How many of the rooms ≥ 4 pC/L had follow-up testing results that were: a. ≥ 4 pCi/L b. < 4 pCi/L c. not tested 'Follow-up' testing means testing done, prior to any radon mitigation, to confirm or verify initial test results in the rooms ≥ 4 pCi/L are, in fact, ≥ 4 pCi/L. If a continuous radon monitor (CRM) was used, indicate concentration duroccupied times. If no follow-up testing was done, write the number of rooms not tested. If follow-up testing will be done in the future, note in comments the planned month and year in the comments section.	ring
Comments:	
13. How many of the rooms ≥ 4 pCi/L: a. were mitigated? b. had other corrective measures? 'Mitigated' means building changes such as adjusting the existing HVAC system, increasing fresh air ventilation rabalancing air flow to rooms, or other such modifications. 'Other corrective measures' could include moving staff our a room and making a room unoccupied or trying to seal radon entry points. If mitigation or other corrective measures will be completed in the future, note in comments the planned month and year in the comments section.	t of
Comments:	
14. How many rooms re-tested after mitigation were: a. ≥ 4 pCi/L b. < 4 pCi/L c. not tested If post-mitigation re-testing will be completed in the future, note the planned month and year in the comments section Comments:	n.



General Instructions

Contact Person for this Form

According to MS 123B.571, radon testing conducted in public school buildings eligible for health and safety (i.e., not charter schools) must be reported to the Minnesota Department of Health.

For the purpose of this form, a building is defined as an occupied facility that has a unique address, including administrative buildings. A building could be a single structure or a complex of structures. For reference, all district owned buildings entered on the Minnesota Department of Education "Facilities Age and Square Footage Report" should be utilized.

- 1. Submit summary information and raw data if either of the following apply:
 - a. Radon testing has been completed in a building since the MDH 'School Radon Testing Survey' dated April 4, 2011, or
 - b. Radon testing was completed at some time previously and your district did not report radon testing in the MDH 'School Radon Testing Survey' dated April 4, 2011.
- 2. Complete one survey for each building tested
- 3. Submit the survey, raw data (e.g., laboratory analysis report) and a building map to MDH by email, to health.indoorair@state.mn.us
- 4. If follow-up testing, mitigation, and/or post-mitigation testing is not yet completed, please submit a completed form and raw data when the work is completed.

Name:_	Kai-	50	1.74		
Phone:_	952-	496-	5046		
Email: _	Kr Smi	+4@ Sh	atopee. Kiz.mn.us		
Mailing .	Address:	1200	Shatopee Town Square	Shakopec,	171155379

Radon Results for Each School Building
1. District Name & Number: Shakoper Public Schools #720
2. School Building Name: Pearson Middle School
3. School Building Address: 917 Dakota St. S.
4. What type of test kit was used? Manufacturer: Landauer Device name: Rad trab 2
Comments
5. When were the test kits retrieved?
Comments
6. How long were the test kits deployed in the rooms?
Comments:
7. Was testing conducted over: a. Weekends? Yes X No b. Holidays or Breaks? Yes No
Comments:
8. Were all frequently-occupied rooms in contact with the ground tested? Yes No _X This includes: 1) rooms on grade and; 2) rooms above unoccupied spaces that are in contact with the ground, such as rooms above storage rooms, crawl spaces, tunnels, and boiler rooms. If only a sample or portion of rooms were tested, then respond with 'no'.
Comments: 3 missing detectors
9. How many frequently-occupied rooms were tested?
Comments: missing 3 so only 40 results
10. How many frequently-occupied rooms were at or above four picocuries per liter (≥ 4 pCi/L)?
Comments:
11. Were test results reported at a school board meeting? Yes X No No If results will be reported at the next meeting, note in comments the month and year of the scheduled meeting in the comments section.
Comments:

12. How many of the rooms ≥ 4 pC/L had follow-up testing results that were:
a. $\geq 4 \text{ pCi/L}$ b. $\leq 4 \text{ pCi/L}$ c. not tested
'Follow-up' testing means testing done, prior to any radon mitigation, to confirm or verify initial test results in those rooms ≥ 4 pCi/L are, in fact, ≥ 4 pCi/L. If a continuous radon monitor (CRM) was used, indicate concentration during occupied times. If no follow-up testing was done, write the number of rooms not tested. If follow-up testing will be done in the future, note in comments the planned month and year in the comments section.
Comments:
13. How many of the rooms ≥ 4 pCi/L: a. were mitigated? b. had other corrective measures? O 'Mitigated' means building changes such as adjusting the existing HVAC system, increasing fresh air ventilation rate, balancing air flow to rooms, or other such modifications. 'Other corrective measures' could include moving staff out of a room and making a room unoccupied or trying to seal radon entry points. If mitigation or other corrective measure(s) will be completed in the future, note in comments the planned month and year in the comments section.
Comments:
14. How many rooms re-tested after mitigation were: a. ≥ 4 pCi/L b. < 4 pCi/L c. not tested f post-mitigation re-testing will be completed in the future, note the planned month and year in the comments section.
Comments:



General Instructions

According to MS 123B.571, radon testing conducted in public school buildings eligible for health and safety (i.e., not charter schools) must be reported to the Minnesota Department of Health.

For the purpose of this form, a building is defined as an occupied facility that has a unique address, including administrative buildings. A building could be a single structure or a complex of structures. For reference, all district owned buildings entered on the Minnesota Department of Education "Facilities Age and Square Footage Report" should be utilized.

- 1. Submit summary information and raw data if either of the following apply:
 - a. Radon testing has been completed in a building since the MDH 'School Radon Testing Survey' dated April 4, 2011, or
 - b. Radon testing was completed at some time previously and your district did not report radon testing in the MDH 'School Radon Testing Survey' dated April 4, 2011.
- 2. Complete one survey for each building tested
- 3. Submit the survey, raw data (e.g., laboratory analysis report) and a building map to MDH by email, to health.indoorair@state.mn.us
- 4. If follow-up testing, mitigation, and/or post-mitigation testing is not yet completed, please submit a completed form and raw data when the work is completed.

	n		-
Contact	Person	for this	Form

Name:_	Kain Smith	
Phone:_	952 - 496. 5046	
Email: _	KrSmith@Shakopee. KIZ. mn. us	
Mailing .	Address: 1200 Shatopee Town Square	Shakopee, MV 55379

Radon Results for Each School Building
1. District Name & Number: Shakopee Public Schools #720
2. School Building Name: Red Oak Elementary 3. School Building Address: 7700 Old Carriage Ct.
3. School Building Address: 7700 Old Carriage Ct.
4. What type of test kit was used? Manufacturer: Landouver Device name: Rad trak 2
Comments
5. When were the test kits retrieved?
Comments
6. How long were the test kits deployed in the rooms?/3 \(\)
Comments:
7. Was testing conducted over: a. Weekends? Yes X No b. Holidays or Breaks? Yes No No
Comments:
8. Were all frequently-occupied rooms in contact with the ground tested? Yes No No This includes: 1) rooms on grade and; 2) rooms above unoccupied spaces that are in contact with the ground, such a rooms above storage rooms, crawl spaces, tunnels, and boiler rooms. If only a sample or portion of rooms were tester then respond with 'no'.
Comments: 7 missing detectors
9. How many frequently-occupied rooms were tested?
Comments: Missing 7 50 only 26 results
10. How many frequently-occupied rooms were at or above four picocuries per liter (≥ 4 pCi/L)?
Comments:
11. Were test results reported at a school board meeting? Yes X No No If results will be reported at the next meeting, note in comments the month and year of the scheduled meeting in the comments section.
Comments:

a. ≥ 4 pCi/L b. < 4 pCi/L c. not tested
'Follow-up' testing means testing done, prior to any radon mitigation, to confirm or verify initial test results in those rooms ≥ 4 pCi/L are, in fact, ≥ 4 pCi/L. If a continuous radon monitor (CRM) was used, indicate concentration during occupied times. If no follow-up testing was done, write the number of rooms not tested. If follow-up testing will be
done in the future, note in comments the planned month and year in the comments section.
Comments:
13. How many of the rooms ≥ 4 pCi/L: a. were mitigated?
Comments:
14. How many rooms re-tested after mitigation were: a. ≥ 4 pCi/L b. < 4 pCi/L c. not tested If post-mitigation re-testing will be completed in the future, note the planned month and year in the comments section.
Comments:



General Instructions

According to MS 123B.571, radon testing conducted in public school buildings eligible for health and safety (i.e., not charter schools) must be reported to the Minnesota Department of Health.

For the purpose of this form, a building is defined as an occupied facility that has a unique address, including administrative buildings. A building could be a single structure or a complex of structures. For reference, all district owned buildings entered on the Minnesota Department of Education "Facilities Age and Square Footage Report" should be utilized.

- 1. Submit summary information and raw data if either of the following apply:
 - a. Radon testing has been completed in a building since the MDH 'School Radon Testing Survey' dated April 4, 2011, or
 - b. Radon testing was completed at some time previously and your district did not report radon testing in the MDH 'School Radon Testing Survey' dated April 4, 2011.
- 2. Complete one survey for each building tested
- 3. Submit the survey, raw data (e.g., laboratory analysis report) and a building map to MDH by email, to health.indoorair@state.mn.us
- 4. If follow-up testing, mitigation, and/or post-mitigation testing is not yet completed, please submit a completed form and raw data when the work is completed.

Contact	Dargan	for this	Danne
Contact	reison	TOP LINS	POPIN

-	Address: 1200 Shakopee Town Square	Shakener 171V 55379
Email:	KrSmith @ Shakopee. K12.mn.us	
Phone:_	952-496.5046	
Name:_	Kain Smith	

Radon Results for Each School Building
1. District Name & Number: Shakoper Public Schools #720
2. School Building Name: Shakopee High School
3. School Building Address: 100 17th are E.
4. What type of test kit was used? Manufacturer: Landa wer Device name: Rad trak 2
Comments
5. When were the test kits retrieved?
Comments
6. How long were the test kits deployed in the rooms?/3 8(days) More than one number can be noted if durations varied
Comments:
7. Was testing conducted over: a. Weekends? Yes X No b. Holidays or Breaks? Yes X No
Comments:
8. Were all frequently-occupied rooms in contact with the ground tested? Yes No _X
Comments: 12 missing detectors
9. How many frequently-occupied rooms were tested?
Comments: Missing 12 so only 37 results
10. How many frequently-occupied rooms were at or above four picocuries per liter (≥ 4 pCi/L)?
Comments:
11. Were test results reported at a school board meeting? Yes \(\frac{1}{2} \) No \(\) If results will be reported at the next meeting, note in comments the month and year of the scheduled meeting in the comments section.
Comments:

12. How many of the rooms ≥ 4 pC/L had follow-up testing results that were: a. ≥ 4 pCi/L b. < 4 pCi/L c. not tested 'Follow-up' testing means testing done, prior to any radon mitigation, to confirm or verify initial test results in those rooms ≥ 4 pCi/L are, in fact, ≥ 4 pCi/L. If a continuous radon monitor (CRM) was used, indicate concentration during occupied times. If no follow-up testing was done, write the number of rooms not tested. If follow-up testing will be done in the future, note in comments the planned month and year in the comments section.
Comments: Room E113A was being remodeled when follow up testing was done
13. How many of the rooms ≥ 4 pCi/L: a. were mitigated? b. had other corrective measures? 6 'Mitigated' means building changes such as adjusting the existing HVAC system, increasing fresh air ventilation rate, balancing air flow to rooms, or other such modifications. 'Other corrective measures' could include moving staff out of a room and making a room unoccupied or trying to seal radon entry points. If mitigation or other corrective measure(s) will be completed in the future, note in comments the planned month and year in the comments section.
Comments:
14. How many rooms re-tested after mitigation were: a. ≥ 4 pCi/L b. < 4 pCi/L c. not tested f post-mitigation re-testing will be completed in the future, note the planned month and year in the comments section.
Comments:



General Instructions

According to MS 123B.571, radon testing conducted in public school buildings eligible for health and safety (i.e., not charter schools) must be reported to the Minnesota Department of Health.

For the purpose of this form, a building is defined as an occupied facility that has a unique address, including administrative buildings. A building could be a single structure or a complex of structures. For reference, all district owned buildings entered on the Minnesota Department of Education "Facilities Age and Square Footage Report" should be utilized.

- 1. Submit summary information and raw data if either of the following apply:
 - a. Radon testing has been completed in a building since the MDH 'School Radon Testing Survey' dated April 4, 2011, or
 - b. Radon testing was completed at some time previously and your district did not report radon testing in the MDH 'School Radon Testing Survey' dated April 4, 2011.
- 2. Complete one survey for each building tested
- 3. Submit the survey, raw data (e.g., laboratory analysis report) and a building map to MDH by email, to health.indoorair@state.mn.us
- 4. If follow-up testing, mitigation, and/or post-mitigation testing is not yet completed, please submit a completed form and raw data when the work is completed.

Cantant	Damas	C 41	TO-
Contact	rerson	ior this	Form

Name:_	Kain Smith	
Phone:	952 - 496. 5046	
Email: _	KrSmith@Shakopee. KIZ.mn.us	
Mailing .	Address: 1200 Shatopee Town Square	Shakopee, 171V 55379

Radon Results for Each School Building
1. District Name & Number: Shakopee Public Schools #720
2. School Building Name: East Jr. High
3. School Building Address: 1137 Marshall Rd.
4. What type of test kit was used? Manufacturer: Landauer Device name: Rad trak 2
Comments
5. When were the test kits retrieved?(month/year) More than one date can be entered if parts of buildings were tested at different times
Comments
6. How long were the test kits deployed in the rooms?(days) More than one number can be noted if durations varied
Comments:
7. Was testing conducted over: a. Weekends? Yes X No b. Holidays or Breaks? Yes No No
Comments:
8. Were all frequently-occupied rooms in contact with the ground tested? YesNoX This includes: 1) rooms on grade and; 2) rooms above unoccupied spaces that are in contact with the ground, such as rooms above storage rooms, crawl spaces, tunnels, and boiler rooms. If only a sample or portion of rooms were tested, then respond with 'no'.
Comments: 4 missing detectors
9. How many frequently-occupied rooms were tested? 34
Comments: missing 4 so only 30 results
10. How many frequently-occupied rooms were at or above four picocuries per liter (≥ 4 pCi/L)?
Comments:
11. Were test results reported at a school board meeting? Yes No No If results will be reported at the next meeting, note in comments the month and year of the scheduled meeting in the comments section.
Comments:

12. How many of the rooms ≥ 4 pC/L had follow-up testing results that were:
a. $\geq 4 \text{ pCi/L}$ c. not tested
'Follow-up' testing means testing done, prior to any radon mitigation, to confirm or verify initial test results in those
rooms \geq 4 pCi/L are, in fact, \geq 4 pCi/L. If a continuous radon monitor (CRM) was used, indicate concentration during
occupied times. If no follow, up testing a continuous factor infollino (CKIVI) was used, indicate concentration during
occupied times. If no follow-up testing was done, write the number of rooms not tested. If follow-up testing will be
done in the future, note in comments the planned month and year in the comments section.
Comments:
13. How many of the rooms \geq 4 pCi/L:
a. were mitigated? b. had other corrective measures?
'Mitigated' means building changes such as adjusting the existing HVAC system, increasing fresh air ventilation rate,
balancing air flow to rooms, or other such modifications. 'Other corrective measures' could include moving staff out of
a room and making a room uncompiled on the said induffications. Office corrective measures could include moving staff out of
a room and making a room unoccupied or trying to seal radon entry points. If mitigation or other corrective measure(s)
will be completed in the future, note in comments the planned month and year in the comments section.
Comments
Comments:
14. How many rooms re-tested after mitigation were:
a. ≥ 4 pCi/L b. ≤ 4 pCi/L c. not tested
If post-mitigation re-testing will be completed in the future, note the planned month and year in the comments section.
The planted mount and year in the comments section.
Comments:
- CAMMAND.



General Instructions

According to MS 123B.571, radon testing conducted in public school buildings eligible for health and safety (i.e., not charter schools) must be reported to the Minnesota Department of Health.

For the purpose of this form, a building is defined as an occupied facility that has a unique address, including administrative buildings. A building could be a single structure or a complex of structures. For reference, all district owned buildings entered on the Minnesota Department of Education "Facilities Age and Square Footage Report" should be utilized.

- 1. Submit summary information and raw data if either of the following apply:
 - a. Radon testing has been completed in a building since the MDH 'School Radon Testing Survey' dated April 4, 2011, or
 - b. Radon testing was completed at some time previously and your district did not report radon testing in the MDH 'School Radon Testing Survey' dated April 4, 2011.
- 2. Complete one survey for each building tested
- 3. Submit the survey, raw data (e.g., laboratory analysis report) and a building map to MDH by email, to health.indoorair@state.mn.us
- 4. If follow-up testing, mitigation, and/or post-mitigation testing is not yet completed, please submit a completed form and raw data when the work is completed.

,	Contact	Dowgon	for th	is Form	
1	Contact	Person	tor th	ic Korm	

	Kain Smith 952-496-5046	
Email: _	KrSmith@Shakopee. KIZ. mn. us	
Mailing .	Address: 1200 Shatopee Town Square	Shakopee, MIV 55379

Radon Results for Each School Building
1. District Name & Number: Shakopee Public Schools #720
2. School Building Name: West Jr. High
3. School Building Address: 200 10th Ave E.
4. What type of test kit was used? Manufacturer: Landquer Device name: Radfra K 2
Comments
5. When were the test kits retrieved?
Comments_
6. How long were the test kits deployed in the rooms?/3 8(days) More than one number can be noted if durations varied
Comments:
7. Was testing conducted over: a. Weekends? Yes X No b. Holidays or Breaks? Yes No No
Comments:
8. Were all frequently-occupied rooms in contact with the ground tested? Yes No _X This includes: 1) rooms on grade and; 2) rooms above unoccupied spaces that are in contact with the ground, such as rooms above storage rooms, crawl spaces, tunnels, and boiler rooms. If only a sample or portion of rooms were tested, then respond with 'no'.
Comments: 6 missing detectors
9. How many frequently-occupied rooms were tested?
Comments: missing 6 so only 35 results
10. How many frequently-occupied rooms were at or above four picocuries per liter (≥ 4 pCi/L)?
Comments:
11. Were test results reported at a school board meeting? Yes \(\setminus \) No If results will be reported at the next meeting, note in comments the month and year of the scheduled meeting in the comments section.
Comments:

12. How many of the rooms ≥ 4 pC/L had follow-up testing results that were: a. ≥ 4 pCi/L b. < 4 pCi/L c. not tested 'Follow-up' testing means testing done, prior to any radon mitigation, to confirm or verify initial test results in those rooms ≥ 4 pCi/L are, in fact, ≥ 4 pCi/L. If a continuous radon monitor (CRM) was used, indicate concentration during occupied times. If no follow-up testing was done, write the number of rooms not tested. If follow-up testing will be done in the future, note in comments the planned month and year in the comments section.
Comments:
13. How many of the rooms ≥ 4 pCi/L: a. were mitigated? b. had other corrective measures? 'Mitigated' means building changes such as adjusting the existing HVAC system, increasing fresh air ventilation rate, balancing air flow to rooms, or other such modifications. 'Other corrective measures' could include moving staff out of a room and making a room unoccupied or trying to seal radon entry points. If mitigation or other corrective measure(s) will be completed in the future, note in comments the planned month and year in the comments section.
Comments:
14. How many rooms re-tested after mitigation were: a. ≥ 4 pCi/L b. < 4 pCi/L c. not tested f post-mitigation re-testing will be completed in the future, note the planned month and year in the comments section. Comments:



School Radon Testing Reporting Form

General Instructions

According to MS 123B.571, radon testing conducted in public school buildings eligible for health and safety (i.e., not charter schools) must be reported to the Minnesota Department of Health.

For the purpose of this form, a building is defined as an occupied facility that has a unique address, including administrative buildings. A building could be a single structure or a complex of structures. For reference, all district owned buildings entered on the Minnesota Department of Education "Facilities Age and Square Footage Report" should be utilized.

Please submit information about the most recent round or cycle of testing conducted for each building, unless this was already reported to MDH in the 4/4/11 survey. We do not need details of prior rounds of testing.

- 1. Submit summary information and raw data if either of the following apply:
 - a. Radon testing has been completed in a building since the MDH 'School Radon Testing Survey' dated April 4, 2011, or
 - b. Radon testing was completed at some time previously and your district did not report radon testing in the MDH 'School Radon Testing Survey' dated April 4, 2011.
- 2. Complete one survey for each building tested
- 3. Submit the survey, raw data (e.g., laboratory analysis report) and a building map to MDH by email, to health.indoorair@state.mn.us
- 4. If follow-up testing, mitigation, and/or post-mitigation testing is not yet completed, please submit a completed form and raw data when the work is completed.

~	-		
Contact	Person	for this	Form

			Shatopee Town Square	Shakoper, 1	- 7/V 55379
Email:	Kr Sm.	+4@ Sh	akopee. KIZ. Mn. US		
Phone:	952-	496.	5046		
Name:	Kai	n 50	1.7+4		

Radon Results for Each School Building
1. District Name & Number: Shakopee Public Schools #720
2. School Building Name: Sun Path Elementary
2. School Building Name: Sun Path Elementary 3. School Building Address: 2250 17th Ave E.
4. What type of test kit was used? Manufacturer: Landquer Device name: Rad trak Z
Comments
5. When were the test kits retrieved?
Comments
6. How long were the test kits deployed in the rooms? // 38 (days) More than one number can be noted if durations varied
Comments:
7. Was testing conducted over: a. Weekends? Yes X No b. Holidays or Breaks? Yes X No
Comments:
8. Were all frequently-occupied rooms in contact with the ground tested? YesNo _X This includes: 1) rooms on grade and; 2) rooms above unoccupied spaces that are in contact with the ground, such as rooms above storage rooms, crawl spaces, tunnels, and boiler rooms. If only a sample or portion of rooms were tested, then respond with 'no'.
Comments: 6 missing detectors
9. How many frequently-occupied rooms were tested?
Comments: missing 6 so only 26 results
10. How many frequently-occupied rooms were at or above four picocuries per liter (\geq 4 pCi/L)? O
Comments:
11. Were test results reported at a school board meeting? Yes X No No If results will be reported at the next meeting, note in comments the month and year of the scheduled meeting in the comments section.
Comments:

If one or more rooms ≥ 4 pCi/L, complete Questions 12-14.

12. How many of the rooms \geq 4 pC/L had follow-up testing results that were:
a. $\geq 4 \text{ pCi/L}$ b. $\leq 4 \text{ pCi/L}$ c. not tested
'Follow-up' testing means testing done, prior to any radon mitigation, to confirm or verify initial test results in those rooms ≥ 4 pCi/L are, in fact, ≥ 4 pCi/L. If a continuous radon monitor (CRM) was used, indicate concentration durin occupied times. If no follow-up testing was done, write the number of rooms not tested. If follow-up testing will be done in the future, note in comments the planned month and year in the comments section.
Comments:
13. How many of the rooms ≥ 4 pCi/L:
a. were mitigated? b. had other corrective measures? 'Mitigated' means building changes such as adjusting the existing HVAC system, increasing fresh air ventilation rate, balancing air flow to rooms, or other such modifications. 'Other corrective measures' could include moving staff out a room and making a room unoccupied or trying to seal radon entry points. If mitigation or other corrective measure(swill be completed in the future, note in comments the planned month and year in the comments section.
Comments:
 14. How many rooms re-tested after mitigation were: a. ≥ 4 pCi/L b. < 4 pCi/L c. not tested If post-mitigation re-testing will be completed in the future, note the planned month and year in the comments section.
Comments:



School Radon Testing Reporting Form

General Instructions

According to MS 123B.571, radon testing conducted in public school buildings eligible for health and safety (i.e., not charter schools) must be reported to the Minnesota Department of Health.

For the purpose of this form, a building is defined as an occupied facility that has a unique address, including administrative buildings. A building could be a single structure or a complex of structures. For reference, all district owned buildings entered on the Minnesota Department of Education "Facilities Age and Square Footage Report" should be utilized.

Please submit information about the most recent round or cycle of testing conducted for each building, unless this was already reported to MDH in the 4/4/11 survey. We do not need details of prior rounds of testing.

- 1. Submit summary information and raw data if either of the following apply:
 - a. Radon testing has been completed in a building since the MDH 'School Radon Testing Survey' dated April 4, 2011, or
 - b. Radon testing was completed at some time previously and your district did not report radon testing in the MDH 'School Radon Testing Survey' dated April 4, 2011.
- 2. Complete one survey for each building tested
- 3. Submit the survey, raw data (e.g., laboratory analysis report) and a building map to MDH by email, to health.indoorair@state.mn.us
- 4. If follow-up testing, mitigation, and/or post-mitigation testing is not yet completed, please submit a completed form and raw data when the work is completed.

-	Contact	Dowgom	Can this	E
1	Contact	Person	tor this	Horm

Name:_	Kain Smith	
Phone:_	952-496-5046	
Email: _	KrSmith@Shakopee. K12.mn.us	
Mailing .	Address: 1200 Shatopee Town Square	Shakopec, MIV55379

Radon Results for Each School Building
1. District Name & Number: Shakopee Public Schools #720 2. School Building Name: Sweeney Elementary
2. School Building Name: Sweeney Elementary
3. School Building Address: 1001 Adams St. S.
4. What type of test kit was used? Manufacturer: Landauer Device name: Radtra K 2
Comments
5. When were the test kits retrieved?
Comments
6. How long were the test kits deployed in the rooms?
Comments:
7. Was testing conducted over: a. Weekends? Yes X No b. Holidays or Breaks? Yes No No
Comments:
8. Were all frequently-occupied rooms in contact with the ground tested? YesNo _X This includes: 1) rooms on grade and; 2) rooms above unoccupied spaces that are in contact with the ground, such as rooms above storage rooms, crawl spaces, tunnels, and boiler rooms. If only a sample or portion of rooms were tested, then respond with 'no'.
Comments: 3 missing detectors
9. How many frequently-occupied rooms were tested?
Comments: missing 3 so only 34 results
10. How many frequently-occupied rooms were at or above four picocuries per liter (≥ 4 pCi/L)?
Comments:
11. Were test results reported at a school board meeting? Yes X No If results will be reported at the next meeting, note in comments the month and year of the scheduled meeting in the comments section.
Comments:

If one or more rooms ≥ 4 pCi/L, complete Questions 12-14.

12. How many of the rooms ≥ 4 pC/L had follow-up testing results that were:
a. ≥ 4 pCi/L b. ≤ 4 pCi/L c. not tested
'Follow-up' testing means testing done, prior to any radon mitigation, to confirm or verify initial test results in those rooms ≥ 4 pCi/L are, in fact, ≥ 4 pCi/L. If a continuous radon monitor (CRM) was used, indicate concentration during occupied times. If no follow-up testing was done, write the number of rooms not tested. If follow-up testing will be done in the future, note in comments the planned month and year in the comments section.
Comments:
13. How many of the rooms ≥ 4 pCi/L:
a. were mitigated? b. had other corrective measures?
'Mitigated' means building changes such as adjusting the existing HVAC system, increasing fresh air ventilation rate, balancing air flow to rooms, or other such modifications. 'Other corrective measures' could include moving staff out o a room and making a room unoccupied or trying to seal radon entry points. If mitigation or other corrective measure(s) will be completed in the future, note in comments the planned month and year in the comments section.
Comments:
 14. How many rooms re-tested after mitigation were: a. ≥ 4 pCi/L b. < 4 pCi/L c. not tested
f post-mitigation re-testing will be completed in the future, note the planned month and year in the comments section.
Comments:

March 7, 2018

Mr. Kain Smith Shakopee Public Schools 1200 Town Square Shakopee, MN 55379



RE:

Shakopee Continuous Radon Monitoring Results

IEA Project # 201710980

Dear Mr. Smith:

As requested by Shakopee Public Schools, IEA assisted with continuous radon monitoring in the following district locations:

Eagle Creek Elementary 129, 113, 110, 108, 103, 104, 105, 111, 114, 101, 130, & Admin Office Jackson Elementary 127 Pearson Middle School 108 Shakopee High School Kitchen

The purpose of the monitoring was to document if radon levels were within an acceptable range during typical work hours.

INTRODUCTION

Long-term radon testing, performed by IEA (see the report dated May 15, 2017), indicated radon levels above the EPA Action Level of 4.0 picoCuries per liter (pCi/L). The Minnesota Department of Health's (MDH's) Best Practices for Radon Measurement in Minnesota Schools and Commercial Buildings recommends follow-up testing in areas where initial testing results are at or above the action level. A continuous radon monitor (CRM) is recommended to determine if elevated levels are present during occupied times. Radon levels can fluctuate with the operation of the ventilation system as well as with changes in barometric pressure. The CRM provides hourly radon readings so that levels can be evaluated for periods while the room is occupied.

EVAULATION CRITERIA

The MDH and the EPA have established a recommended Action Level in frequently occupied areas of 4.0 picoCuries per liter (pCi/L) for an annual average. The average radon level over each work day was compared to the Action Level.

RESULTS & DISCUSSION

From December 14, 2017 through February 26, 2018, the continuous radon monitoring was conducted in the district locations. The CRM was placed in each room for about 72 hours; the MDH recommends a minimum of 48 hours. The times of day when these rooms were not occupied (e.g., nights and weekends) were not included in the "Day Ranges" calculated averages. For comparison data, an "Overall Average" is displayed that did include all monitoring data. The hourly CRM data (hard copy tapes) is provided in Appendix A. The buildings floor plan maps with the locations of the continuous radon monitor locations marked are provided in Appendix B.

A summary of the continuous radon monitor data is provided in the following tables: Long-Term testing results are shown in reference

Eagle Creek Elementary:

Continuous Radon Monitoring Results – December 14, 2017 to February 13, 2018

Date Range	Room#	¹ Day 1 Range (Ave.) (pCi/L)	¹ Day 2 Range (Ave.) (pCi/L)	¹ Day 3 Range (Ave.) (pCi/L)	² Overall Average (pCi/L)	Results from the Long-Term Testing (pCi/L)
12/14/17 to 12/19/17	129	0.39	0.91	0.86	5.1*	14.4
1/4/18 to 1/8/18	113	0.87	0.55	NA	4.9*	9.4
1/8/18 to 1/10/18	110	0.64	0.66	1.15	2.5	6.6
1/10/18 to 1/12/18	108	0.80	0.71	2.42	3.5	5.3
1/12/18 to 1/17/18	103	0.16	0.31	0.38	3.7*	5.0
1/17/18 to 1/19/18	104	0.34	1.11	NA	3.9	5.0
1/19/18 to 1/25/18	105	0.64	0.21	0.17	3.4*	4.9
1/25/18 to 1/31/18	111	0.26	0.56	0.33	4.2*	4.8
1/31/18 to 2/2/18	114	0.68	0.48	1.00	2.6	4.6
2/2/18 to 2/6/18	101	0.20	0.53	NA	3.3*	4.1
2/6/18 to 2/8/18	130	0.59	0.53	0.50	2.6	4.1
2/8/18 to 2/13/18	Admin Office	0.44	0.35	0.33	4.9*	5.1

Readings during occupied times: 7 a.m. to 5 p.m.

²Overall average is average for entire test period including when room was not occupied

*Includes an entire weekend, Saturday and Sunday

pCi/L - picoCuries per liter of air

Jackson Elementary:

Continuous Radon Monitoring Results – February 13 to 15, 2018

Date Range	Room#	¹ Day 1 Range (Ave.) (pCi/L)	¹ Day 2 Range (Ave.) (pCi/L)	¹ Day 3 Range (Ave.) (pCi/L)	² Overall Average (pCi/L)
2/13/18 to 2/15/18	127	1.16	1.74	NA	6.2

Results from the Long-Term Testing (pCi/L) 4.9 & 4.2

²Overall average is average for entire test period including when room was not occupied

pCi/L - picoCuries per liter of air

Pearson Middle School:

Continuous Radon Monitoring Results - February 22 to 26, 2018

	10000 07	estangua umbers Bir ki ASI (190	e etarlielle brook el coll en esacen	tion, 12 and 90 or 1	2 majord limbor Limed levelor is
Date Range	Room#	¹ Day 1 Range (Ave.) (pCi/L)	¹ Day 2 Range (Ave.) (pCi/L)	¹ Day 3 Range (Ave.) (pCi/L)	² Overall Average (pCi/L)
2/15/18 to 2/19/18	108	1.10	1.00	1.25	5.4*

Result from the Long-Term Testing (pCi/L) 4.1

Readings during occupied times: 7 a.m. to 5 p.m.

²Overall average is average for entire test period including when room was not occupied

*Includes an entire weekend, Saturday and Sunday

pCi/L - picoCuries per liter of air

Shakopee High School:

Continuous Radon Monitoring Results - February 20 to 22, 2018

Albert of Debut	7.1405; 184 5.0 d 14 d 10 d	¹ Day 1 Range	¹ Day 2 Range	¹ Day 3 Range	² Overall Average
Date Range	Room #	(Ave.) (pCi/L)	(Ave.) (pCi/L)	(Ave.) (pCi/L)	(pCi/L)
2/20/18 to 2/22/18	Kitchen	0.38	0.82	1.40	0.7
¹ Readings during or	cupied tim	es: 7 a.m. to 5 p.m	1.		

Results from the Long-Term Testing (pCi/L) 15.0

²Overall average is average for entire test period including when room was not occupied

pCi/L - picoCuries per liter of air

Discussion of Results

- The "Day Ranges" calculated averages show on average ranging from 0.16 to 1.85 picoCuries per liter (pCi/L); all below the EPA Action Level. These average radon levels are all over the working hours of the days during the work-week, the range of occupied time from 7am to 5 pm, in the locations denoted.
- The "Overall Average" that includes all monitoring data (including nights and weekends) ranged from 0.7 to 6.2 picoCuries per liter (pCi/L).

CONCLUSIONS & RECOMMENDATIONS

The results of the continuous radon monitoring indicate that radon levels in all the locations tested are below the action level during the working hours of the days during the work-week, the range of occupied time from 7am to 5 pm. The testing was performed during the Winter season of 2017/2018 so the testing is representative of "worst case" conditions.

Recommendations:

- Continue with the HVAC settings used for working hours of the days during the work-week, the range of occupied time from 7am to 5 pm, for these tested locations.
- For occupied time outside of the working hours of the days during the work-week, the range of occupied time from 7am to 5 pm, such as nights and weekends, when the buildings will be occupied for various functions in the tested rooms, IEA recommends implementing the HVAC settings used for working hours of the days during the work-week, the range of occupied time from 7am to 5 pm.
- The known methods for the radon reduction could include processes such as either diluting or pressurizing these areas to limit radon entry, or by implementing a combination of the two techniques. Increasing fresh air while keeping the return air unchanged or reduced can help pressurize work areas to limit radon entry. Knowledge of your systems and your buildings will guide your adjustments.
- For any future adjustments made to the HVAC system in the rooms tested, IEA recommends repeating this testing, keeping in mind to plan any retested to be during the winter heating season (i.e. under "closed" conditions) which is typically "worst case" conditions.
- Per Minnesota Statutes, section 123B.571, school districts are now required to report radon test results at a school board meeting and report results to the MDH. IEA is able to assist with presenting results to the school board, and the MDH reporting.

GENERAL COMMENTS

The analysis and opinions expressed in this report are based upon data obtained from continuous radon monitoring at district locations and are representative of those locations and time periods sampled. This report does not reflect variations in conditions that may occur across the site, property, or facility. Actual conditions may vary and may not become evident without further assessment.

The report is prepared for the exclusive use of our client for specific application to the project discussed and has been prepared in accordance with generally accepted radon testing practices. Other than as provided in the preceding sentence and in our proposal #6419 dated September 14, 2017, regarding radon testing services, including the General Conditions attached thereto, no warranties are extended or made. IEA appreciates the opportunity to submit this analysis to Shakopee Public Schools.

Should you require additional radon testing or have any questions regarding radon or any other health- or safety-related concerns, please do not hesitate to contact our office.

Sincerely,

Sincerely, IEA, INC.

Ben LaFond, CSPI EHS Account Manager

BL/ep 3/07/18

Enc.

Karen Weiblen
EHS/IEQ Consultant

Appendix A

Continuous Radon Monitor Hourly Data

Λ
REPORT
TEST
PADON
V

000000000	ადიდდ 4 4 - 4 6	თთთითი ⊶ისისადი	დთ <u>ი</u> . აიო		, ८, ७, ८, ८, ७, , ८, ७, ७, ७, ७, ७, ७, ७, ७, ७, ७, ७, ७, ७,	r. r. a a a r. a r. a a a a a a a	8.00 0.07 0.04 0.05 0.05 0.05
855 855 855 855 855 855 855 855 855 855	00000 04004	88884444 8888444	2 4 4 4 6 4 6 4 6 4 6 4 6 4 6 4 6 4 6 4	4 C C C C C C C C C C C C C C C C C C C	្ត មិន្តិក្រុម្ភិស្ត្	0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	68 69 71 72 73
Office.							
	2/08/19 10:45	.380	# -B tr.		88888888		
ORT V	2/08	510	11 (24 (3))	00000000000000000000000000000000000000	222222222222222222222222222222222222222	70000000 70000000 70000000	888888 6686888
REPO			E X		000000		
EST		Ę	18	`			\
< RADON TEST REPORT	DATE	1 .2.5	70 1	- 90-0-		30000000000000000000000000000000000000	
7 P	START I	0Z 1→	1 1	⊶ N w A ru a	្រេយ៣០ហ្ម	24100500	22 22 22 22 22 22

74 75 76 77 78 80 80 80 80 80 80 80 80 80 80 80 80 80	456565555555444444211	28.9 28.9 29.0	000111111111111111111111111111111111111
116	6.1	0 29.5	61
117	3.5	0 29.5	64

Elapsed Time (min.) 7020
Total Count 14594
Avs. (pC1/1) 4.9

27 5.5 3 28.7 64 28 5.8 3 28.7 64 29 5.9 3 28.7 64 30 5.5 3 28.7 64	41 3.3 42 2.3 43 2.7 44 2.1 45 3.0 47 48 2.7 48 2.7 50 3.1 51 4.7 50 3.1 51 52 4.7 51 52 5.8 52 5.8 53 5.8 54 5.9 55 5.8 57 6.9 58 7.0 60 4.7 62 63 4.7 63 6.9 64 5.3 65 6.9 67 70 71 7.1 72 73 74 75 76 77 78 980 81 8.7 78 88 83 84 85 86 87 88 89 90 91 92 93 94 94 94 94 94 94 94 94 94 94 94 94 94	4 29.0 64 4 29.2 64 3 29.2 64 3 29.2 64 3 29.3 64 3 29.3 65 3 29.3 66 3 29.2 64 4 29.2 64 4 29.2 64 4 29.2 64 4 29.2 64 5 29.2 64 2 29.0 64 2 29.0 64 2 29.0 64 2 29.0 65 2 29.0 64 2 29.0 65 2 29.3 75 0 29.3 75 0 29.3 75 0 29.3 72 0 29.3 72 0 29.3 72 0 29.3 72 0 29.3 72 0 29.3 72 0 29.3 66 2 29.3 66 2 29.3 66 2 29.3 66 3 29.3 66 3 29.3 64 3 29.3 64
27 5.5 3 28.7 64 28 5.8 3 28.7 64 29 5.9 3 28.7 64 30 5.5 3 28.7 64 31 5.2 4 28.7 64 32 4.9 4 28.7 64 33 4.7 4 28.7 63 34 5.5 4 28.9 63 35 3.6 4 28.9 63 36 3.3 4 28.9 63 37 3.4 4 28.9 63 38 3.4 4 29.0 64	92 3.1 93 2.1 94 1.4 Elapsed Time Total Count Ave. (PCI/1)	3 29.3 63 2 29.3 64 0 29.6 70 0 29.6 73 (min.) 5640 8328
39 2.6 4 29.0 64 40 3.8 4 29.0 64		

< RADON TEST REPORT >	41 5.2 2 29.5 60 42 4.5 2 29.3 60	
EC Clossroom 1) 43 4.5 2 29.3 60 44 5.0 2 29.3 60 45 5.3 2 29.3 60	3
START DATE 1/12/18	46 5.3 2 29.3 60 47 4.9 2 29.3 60	3
START TIME 12:31	48 5.9 2 29.2 63 49 5.5 2 29.2 63 50 6.0 2 29.0 63	3
OPERATOR SOP	51 5.6 2 29.0 63 52 5.2 2 29.0 63 53 5.3 2 29.0 63	3 3 3
ERIAL NO CRM5106160 OF (CPM/pCi/l) .388 NG (pCi/l) .5	54 6.8 2 29.8 63 55 5.6 3 29.0 63 56 5.4 3 29.8 63 57 6.1 3 29.0 63	3
Hr Conc. / L RH B/P des PCI/l B % "He F	58 5.1 3 29.0 63 59 4.5 3 29.0 53 60 3.7 3 29.2 63 61 3.8 3 29.2 63	3
1 .2 / 0 29.6 70 2 .2 0 29.6 69 3 .1 0 29.6 69 5 .2 0 29.8 67 6 1.7 0 29.6 65 7 3.3 0 29.6 62 9 5.8 0 29.6 61 11 6.5 2 29.6 61 12 7.2 2 29.5 60 13 7.5 3 29.5 60 14 7.2 3 29.5 60 14 7.2 3 29.6 61 17 4.4 2 29.6 61 18 4.8 2 29.6 62 19 4.5 2 29.6 62 20 4.0 2 29.6 62 21 0.7 2 29.6 62 22 4.4 2 29.6 62 23 3.9 2 29.6 62 24 3.4 2 29.6 62 25 4.4 2 29.6 62 27 5.5 2 29.6 62 27 5.5 2 29.6 62 28 5.1 2 29.6 62 27 5.5 2 29.6 62 28 5.1 2 29.6 62 29 4.2 2 29.6 62 27 5.5 2 29.6 62 28 5.1 2 29.6 62 29 4.2 2 29.6 62 21 3.8 2 29.6 62 23 3.9 2 29.6 62 24 3.4 2 29.6 62 25 4.4 2 29.6 62 26 6.0 2 29.6 62 27 5.5 2 29.6 62 28 5.1 2 29.6 62 29 4.2 2 29.6 62 29 4.2 2 29.6 62 29 4.2 2 29.6 62 29 5.5 63 30 5.2 29.6 63 31 3.8 2 29.6 63 32 4.4 2 29.6 63 33 5.2 29.6 63 33 5.2 29.6 63 34 5.4 2 29.6 63 35 4.9 2 29.5 63 36 4.7 2 29.5 63 37 4.1 2 29.5 63 39 4.8 2 29.5 63 39 4.9 2 29.5 63	61	

(03 car

4101# coordal dearly

RT DATE 1/17/18

RT TIME ▼ 12:42

RATOR _____

IAL NO			CF	M5106	160	
(CPM/pCi/l)					380	
(pCi/l)					.5	
:=		===	===	=====		====
	Conc.	1	L	RH	B/P	dea
	PCi/1		B	%	"Hø	F
	.6	1		0	29.3	69
	. 1			1	29.3	69
	.3 .1			1	29.3	68
	. 1			2	29.2	68
	.6			2	29.2	66
	1.2			3	29.0	65
	1.6			3	29.0	64
	2.9			4	29.0	64
	4.4			5	29.0	63
į []	5.8			6	29.0	62
	6.1			6	29.0	61
10	7.9 7.7			7	29.0	61
10	7.7			7	29.0	61
. +	8.5			7	29.0	61
15	9.5			8	28.9	60
: 18	8.2			8	28.7	60
	8.3			8	28.7	60
18	7.3			8	28.9	61
] 7 20 44	6.3			7	28.9	54
20	3.3			6	28.9	65
2 :	2.6			8	29.0	66 68
	1.4			10 10	29.0 29.0	69
	.5			10	29.0	68
	.5			11	28.9	63
•	.8			13	28.9	68
	.2			13	28.9	67
	. 4			ک ۱	20.7	01

28	.5	13 28.9	67
29	.5	13 28.9	65
30	.5	13 28.9	36
21	1.9	13 28.7	65
32	2.2	14 28.7	64
33	4.5	14 28.7	€4
34	4.1	14 28.7	63
35	6.2	14 28.7	62
36	€.5	15 28.7	62
37	6.0	15 28.7	62
38	7.6	15 28.7	51
39	9.1	15 28.7	61
40	8.8	15 28.7	61
41	7.5	15 28.7	61
42	8.2	14 28.6	62
43	5.2	13 28.6	64
44	3.1	12 28.7	66
45	2.2	13 28.7	68
46	.9	14 28.7	69
47	.5	14 28.7	68

Elapsed Time (min.)	2820
Total Count	4785
Avg. (pCi/l)	3.9
==========	

CRADON TEST REPORT > I/D Calchool Claure /O! START DATE 1/19/18 START TIME 12:39 OPERATOR CRM5106160 C/F (CPM/PCi/1) .380 BKG (PCi/1) .5 Hr Conc. / L RH B/P das PCi/1 B % "Hs F	40 3.9 22 28.7 58 41 4.2 22 28.7 59 42 5.4 22 28.7 59 43 3.8 22 28.9 59 44 4.5 22 28.9 59 45 4.7 22 28.9 59 46 4.6 21 28.9 60 47 4.5 21 28.7 59 48 5.2 21 28.7 59 49 4.4 22 28.7 59 50 4.1 22 28.7 59 51 4.0 22 28.7 59 51 4.0 22 28.7 59 52 4.8 22 28.7 59 53 3.7 22 28.7 59 54 4.5 22 28.7 59 55 4.5 22 28.7 59 56 3.4 22 28.7 59 57 4.0 22 28.7 59 58 4.5 22 28.7 59 59 3.5 22 28.7 60 60 4.0 21 28.7 60
1 .9 / 17 28.6 65 2 .7 19 28.5 64 3 .5 20 28.5 64 4 .5 21 28.5 64 5 .6 22 28.6 63 6 .9 23 28.6 62 7 1.1 23 23.6 62 8 2.3 23 28.6 61 9 2.9 22 28.6 61 10 4.6 22 28.7 51 11 4.4 22 28.7 61 12 4.7 22 28.7 61 12 4.7 22 28.6 60 14 4.9 22 28.6 60 15 6.1 21 28.6 60 16 6.2 21 28.6 60 17 6.5 21 28.7 59 20 8.2 21 28.7 58 <	61

```
99
                     . 1
                                 5 29.0
           100
                     . í
                                            25
                   .0
1.1
1.7
                                 5 29.0
           101
                                 5 29.0
          102
                                           59
                                3 29.2
          103
                                23.2
          104
                   2.3
                                           E:
                              10 29.0
           15
                   3.7
                                          60
                              11 29.0
           16
                  5.0
                                          SD
                              11 29.5
          37
                  4.7
                                          ευ
                              12 29.0
          18
                  7.2
                                         59
                              12 29.0
                 5.8
7.7
          03
                                         59
                             10 29.0
        . 10
                                         58
                             13 29.0
                 6.9
5.9
                                         58
                            14 29.0
14 29.0
        -12
                                         58
                7.7
                                        58
         14
                            14 29.0
                5.1
                                        50
                            12 29.2
         15
                1.7
                                        80
       .16
                            8 29.2
7 29.3
                 .9
                                       E .;
       117
                           7 29.3
7 29.3
7 29.3
8 29.2
8 29.2
                 ٠5
                                       65
       -18
                . 1
                                       66
      19
                .4
                                      66
       20
                . 1
                                      55
       21
                                     65
38
65
                .2
                          10 29.3
      22
               .0
                         11 29.2
      23
               .0
                         12 29.2
     24
              - 1
                                     54
                        12 29.2
     25
              - 1
                                    Eq
                        13 29.2
15 29.2
     26
            1.4
                                    ნვ
     27
                       15 29.2
17 29.2
17 29.0
                                    62
    28
            1.6
                                   6!
    38
            4.0
                                   81
    30
           3.9
                                   60
   31
                       17 29.0
           4.2
                                  \varepsilon_{C}
                      17 29.0
   32
          5.1
                                  59
                      17 29.0
 133
          5.0
                                  59
                     17 29.0
18 25.0
  34
          7.7
                                 59
  35
         7.4
                                 53
                    18 29.0
18 29.0
  36
         7.0
                                 50
 37
         6.4
                                58
                    13 29.0
 38
         5.0
                                53
                   17 29.2
14 29.2
 33
         2.1
                                60
 10
         ٠٤
                               64
                   12 29.3
41
         .0
                               56
                   14 29.3
42
         .2
                               SC
43
                   16 29.3
         .2
                  15 29 3
```

lassed Time (min.) 8530
Otal Count 13052
Va. (PCIVI) 3.4

In Blongrapm 108 E.K.

START TIME 12:16

OPERATOR CONTRACTOR

3ERIAL NO.- CRM5106160 C/F (CPM/PCi/l) .380 BKG (PCi/l) .5

Hr Conc. / L RH B/P deg PCi/l B % "Hg F

1 .5 22 28.6 67 2 .9 22 28.6 67 4 1.0 21 28.6 67 5 .7 22 28.6 67 6 .1 23 28.6 67 7 .5 22 28.6 67 10 2.6 23 28.6 67 11 2.6 22 28.6 67 12 3.9 22 28.6 67 13 6.2 22 28.6 67 14 8.2 21 28.7 67 15 9.0 20 28.7 67 16 8.5 20 28.7 67 17 11.0 20 28.9 67 18 10.0 19 28.9 67

Elapsed Time (min.) 2520 4313 of (pCl/1)

1/0 Classoom/10

18

19

20

21

22

23

5.7

6.4

7.4

7.0

7.1

6.5

10 29.2 68

10 29.2 68

10 29.2 68

10 29.2 68

10 29.2 68

9 29.2 68

START DATE 1/08/18	
START TIME 8:21	04
OPERATOR DEP	24 2.7 10 29.2 67 25 2.0 11 29.2 67 26 .2 14 29.2 68 27 .6 14 29.2 68
SERIAL NO CRM5106160 C/F (CPM/pCi/l) .380 3KG (pCi/l) .5 Hr Conc. / L RH B/P dgg pCi/l B=% "Hg F	28
1 2.2 6 29.0 69 2 1.5 10 29.2 69 3 .3 / 10 29.2 69 4 .5 12 29.3 70 5 .3 11 29.2 71 6 .2 12 29.3 72 7 .3 13 29.3 72 8 .0 13 29.0 73 9 .1 10 29.3 72 10 .3 9 29.3 71 11 .7 9 29.2 70 12 .8 9 29.2 69 13 1.6 10 29.2 69 14 3.1 10 29.2 69 15 3.8 10 29.2 69 16 4.0 10 29.2 68	34 1.4 13 29.2 72 35 1.7 13 29.0 71 36 2.0 14 29.0 70 37 2.2 14 28.9 69 38 3.4 14 28.9 69 39 4.0 13 28.9 69 40 3.8 13 28.9 69 41 4.0 13 28.9 68 42 4.9 13 28.9 68 43 4.5 13 28.9 68 44 4.8 13 28.7 67 45 4.0 13 28.7 67 46 4.6 13 28.7 67 47 3.3 14 28.7 67 48 1.9 15 28.7 67 49 1.6 17 28.7 67 50 .7 20 28.7 69
17 5.4 10 29.2 68	Flores I Time (m.) 0000

Elapsed Time (min.)

Total Count

Avg. (PCi/l)

3000

3509

< RADON TEST REPORT >	49 50	6.7 7.5 7.5	23 29.0 61 23 29.0 61 23 29.0 61
10 E.C. Clesonson 111	51	7.8	22 29.0 61
	52	6.6	22 29.0 62
	53	7.3	21 29.0 62
START DATE 1/25/18	54	8.9	22 29.2 61
	55	8.5	22 29.2 61
	56	8.4	22 29.2 61
START TIME 12:12	57 58	7.1 7.5	22 29.0 60
OPERATOR Directicle	59	7.1	22 29.0 60
	60	6.7	22 29.0 60
	61	6.2	21 29.0 59
SERIAL NO CRM5136160 C/F (CPM/pCi/l) .38C BKG (pCi/l) .5	62 63 64 65 66	6.6 6.7 5.4 6.8	21 29.2 59 21 29.2 59 21 29.2 59 21 29.2 58 21 29.2 58
Hr Conc. / L RH B/P dec PCi/l B % "Hs F	67 68 69	6.0 4.5 4.2	20 29.2 59 16 29.3 61 18 29.3 61
1 .3 17 29.2 66	70	3.5	17 29.5 61
2 .2 18 29.2 66	71	3.7	17 29.3 60
3 .0 19 29.2 66	72	4.0	17 29.5 61
	73	4.7	17 29.3 60
5 .1 18 29.0 55	74	3.8	17 29.3 60
	76	4.1	17 29.3 60
7 1.5 19 29.8 64	76	3.3	16 29.5 61
	77	4.3	16 29.3 60
9 8.4 20 29.0 63	78	5.2	16 29.3 59
	79	4.1	16 29.3 60
10 4.4 20 28.9 62	80	2.8	15 29.5 61
11 4.4 20 28.9 61	81		15 29.3 60
12 6.5 20 28.9 61	82	3.5	15 29.3 60
13 5.6 20 28.9 61	83	4.1	15 29.3 59
14 6.4 20 28.7 S1 15 7.2 20 28.7 61	84	4.0	15 29.3 80
17 7/9!!!!!31!39/7!!71	85	3.4	14 29.3 60
!17!!!!9/5!!!!!31!39/7!!71	86		14 29.3 60
19 9/3 31 39/7 71	87	4.3	13 29.5 60
19 5/7 16 28.7 65	88		13 29.3 59
20 2.1 13 28.7 69	90	3.6	13 29.5 60
21 1.1 / 12 28.9 70	90	4.4	13 29.3 60
22 .8 16 28.7 69	91	2.8	10 29.5 63
	92	1.6	7 29.6 66
24 .5 18 28.7 67	93	.9	3 29. 3 67
	94	.9	5 29.6 63
26 .6 25 28.7 67	95 98	.3	4 29.8 7 1 2 29.6 69
27 .7 27 28.7 68 28 .2 28 28.7 50	97 98	.1 .1 .2	2 29.6 67
29 .3 27 28.7 66 30 .6 26 28.7 66	99	.0	1 29.6 67
31 2.5 26 28.7 65	100	.2	3 29.6 68
32 3.6 27 23.7 64	101		2 29.6 66
33 6.1 27 28.7 64	102	.5	3 29.5 65
34 8.3 27 28.7 63	103	1.5	4 29.5 64
35 8.3 27 28.7 63	104	2.0	5 29.5 63
36 7.7 27 28.9 62	105	3.0	6 29.5 62
37 6.6 27 28.9 52	106	3.9	7 29.5 61
	107	4.6	7 29.5 61
39 6.8 26 28.9 61	108	5.4	8 29.5 61
	109	4.2	8 29.3 60
41 7.8 25 29.0 61	110 111	5.8	8 29.2 50 9 29.2 59
42 7.7 25 29.0 61	112	7.3	9 29.2 59
43 7.6 25 29.0 61	113	6.9	9 29.2 59
44 7.8 24 29.0 61	114	7.5	9 29.2 59
45 8.9 24 29.6 31	115	4.7	6 29.3 63
46 6.8 24 25 0 £1	A (A) 42	7.1	0 27.0 03

```
18
        1.5
                    3 29.5
                             70
 19
         .9
                    3 29.3
                             70
         .5
                    2 29.2
120
                             67
121
                   3 29.2
         .4
                             67
                   5 29.0
4 29.0
122
         .3
                            67
123
         . 7
                            56
124
                   6 28.9
                            66
         .3
125
                   6 28.7
                            65
         . 1
         .8
                   7 28.7
                            64
                   7 28.7
127
        1.9
                            63
128
        3.9
                   3 28.7
                            62
        4.7
129
                   8 28.6
                            51
        5.5
                   9 28.6
                            81
130
                   9 28.6
131
                            51
132
        5.9
                   9 28.6
                            51
        7.6
                  10 28.5
133
                            60
        7.0
134
                  10 28.5
                            69
135
        8.3
                  10 28.5
                            50
136
        7.9
                  11 28.5
                            50
137
        6.8
                  11 28.5
                            60
                  11 28.5
138
        7.9
                            60
189
        4.5
                  10 28.7
                            64
140
        2.6
                   8 28.9
                            67
```

Elapsed Time (min.) 8400
Total Count 15321
Avs. (pCi/l) 4.2

Cont.

1)1

i/d Closset Start date Start time	1/04/18 8:21	45 48 47 48 49 50	6.6 5.1 6.1 7.7 6.3 6.3	3 29.5 58 3 29.5 58 3 29.5 58 3 29.5 50 3 29.5 58 3 29.3 58 3 29.3 58
OPERATOR &	&P	52 53 54 55 56 57	5.7 6.7 7.9 7.5 6.7 8.8	3 29.3 58 3 29.3 58 3 29.2 58 3 29.2 58 3 29.2 59 3 29.2 59
BKG (pCi/l)	* .5	58 59 60 61	7.4 7.9 8.1 6.1	3 29.2 50 4 29.0 59 4 29.0 58
Hr Conc. PCirl 1 2.9 2 34 1.0 2 34 1.0 3 4 1.3 6 7 8 9 6 .5 11 1.3 12 1.3 13 2.8 15 3.8 17 18 3.8 19 3.7 16 3.8 17 18 3.7 22 23 2.7 24 25 1.2 25 26 27 28 29 31 32 26 27 28 29 31 31 32 33	LRH B/P des B % "Hs F 1 29.6 66 2 29.5 68 2 29.6 70 2 29.6 71 2 29.6 72 1 29.6 70 2 29.6 71 2 29.6 70 0 29.3 64 0 29.3 62 1 29.3 58 2 29.3 58 2 29.3 58 3 29.3 58 3 29.3 58 3 29.3 58 3 29.3 58 3 29.3 58 3 29.3 58 3 29.3 58 3 29.3 58 3 29.3 58 0 29.6 66 0 29.6 66 0 29.6 66 0 29.6 66 0 29.6 66 0 29.6 66 0 29.6 66 0 29.6 65	62 64 65 67 67 77 77 77 77 77 77 77 77 77 77 77	6.7 7.3 6.8 7.5 7.5 7.6 7.0 8.1 7.0 8.1 7.0 8.1 7.2 7.4 7.8 8.3 8.3 8.3 8.4 6.9 7.1 8.3 8.4 6.9 8.6 8.6 8.6 8.6 8.6 8.6 8.6 8.6 8.6 8.6	4 29.0 58 4 28.9 58 4 28.9 58 4 28.9 58 4 28.9 58 5 28.7 58 5 28.7 58 5 28.7 58 5 28.7 58 5 28.7 58 5 28.7 58 5 28.7 58 5 28.7 58 5 28.7 58 6 28.7 58 6 28.7 58 6 28.7 58 6 28.7 58 6 28.7 58 6 28.7 58 6 28.7 58 6 28.7 58 6 28.7 58 6 28.7 58 6 28.7 58 6 28.7 58 6 28.7 58 6 28.7 59 7 28.7 59 8 28.7 59 8 28.7 59 8 28.7 59 8 28.7 59 8 28.7 59 8 28.7 59 8 28.7 59 8 28.7 59 9 28.7 59

Earle Brook Massersom 114 < RADON TEST REPORT >

1/31/18	0:37	
ART DATE	ART TIME	BRATOR BASE

*	8 28.9 67 9 29.0 70 7 29.0 70 7 29.0 70 10 29.0 70 10 29.0 71 10 29.0 71 10 29.0 71 10 29.0 71 10 29.0 67 9 29.2 67
7 P	20.7.0.847.2.4.8.8.2.7.2.8.4.8.8.8.8.4.4.8.8.8.8.4.4.8.8.8.8.8
PC1/1	11 12 10 10 10 11 11 11 11 11 11 12 13 14 11 16 17 17 18 18 18 18 18 18 18 18 18 18 18 18 18

99	ω ω	20	70	69	<u></u> 1	72	72	70	69	<u>რ</u>	9	8	80	99	63	67	8	6	9	67	99	99	99	99	
23	83	29.5	29	29.	29	о С	69	23	ы Ф	29	80	29	29	8	29.	80	29	8	29	8	8	8	29	29.	
co	4	ന	F-1	0	-	CA	C)	-	ω.		CA	CV	LVI	U	CA	CO	C)	C.J	CJ	.,		•	_	_	
9.	6.	ω.	9.	ი.		4.	0.	.	œ.									•	•		•	•	•		
25	26	27	28	29	30	31	ŭ	<u>ස</u>	34	വ	36	(~ (?)	(C)	33	40	41	42	40	44	45	46	47	4 0	<u> 2</u>	

2940	3550	2.6	11
(min.)			
ed Time	Count	(PC1/1)	
Elapsed	Total	Ave.	11 11 11 14

I/D _____

START DATE 12/14/17

467 89 0 1 2 3 4 5 6 6 6 6 6 6 7 7 7 7 7 7 7 8 9 8 8 8 8 8 8 9 9 9 9 9	7.7.7.7.6.6.5.6.6.5.6.6.6.5.5.6.6.7.6.5.5.6.7.6.7	17 28.7 61 18 28.7 61 18 28.9 61 18 28.9 61 18 28.9 61 18 28.9 61 18 28.9 61 19 28.9 61 19 28.9 61 19 28.9 60 19 28.9 60 19 28.9 60 19 28.9 60 19 28.9 60 19 28.9 60 19 28.9 50 19 28.9 50 19 28.9 50 18 28.9 50

STAR	T TIME			ğ	9:59			
OPER	OPERATOR							
C/F BKG	AL NO (CPM/pC (pCi/l)	i/l)			.380 .5			
111	pCi/l	В		"Ha	F			
1 2 3 4 5 6 7 8 9 10 11 12 13 14 14 15 16 17 18 19 20 21 22 22 22 22 22 23 33 33 33 33 33 34 44 44 44 44 44 44 44	78512035631384852168546776754108722023876255		55554444356789001111222119888888889011223455667777777777777777777777777777777777	29.2 29.2 29.3 29.3 29.3 29.2 29.0 29.0 29.0 29.0 29.0 29.0 29.0	70 68 66 55 64 64 63 62 61 61 53 66			

```
97
                                .4
                 98
                                                13 28.8
            39
100
101
                                .6
                                       12 28.9
13 28.5
14 29.7
14 28.7
15 28.7
15 28.7
17 28.7
18 28.7
19 28.6
20 28.6
21 28.6
21 28.7
21 29.7
                                                12 28.9
                               .5
                                                                   68
                              .9
                                                                  59
                              .6
            102
                                                                 69
                              . I
            103
                                                                 69
                             . 5
                       2.3
           104
                                                                63
           105
                                                                69
          106
                                                              67
68
         107
                 4.9
7.1
7.6
6.6
6.9
8.8
7.8
                                                          65
64
64
64
65
        108
        109
       110
      111
     112
                                       21 28.7
                               22 28.7
22 28.7
23 28.7
23 28.7
23 29.9
21 20.9
17 29.0
16 29.0
15 29.0
19 29.0
     113
                                      22 23.7
                                                          63
    114
                                                        62
   115
 115
117
118
               7.5
                                                        61
                                                       61
                                                   61
63
68
68
68
 115
               1.2
120
                 .8
121
                -1
                                                   59
                                                   59
```

Elapsed Time (min.) 726C Total Count 15505 Avg. (pCi/l) 15505 5.1

< RADON TEST REPORT >

170 Epplescen alassagen 130

2/06/13 8:51 START DATE START TIME

OPERATOR OF

CRM5105150 1 1 1 1 1 C/F (CPM/PC1/1) SERIAL NO. -BKG (PCi/1) Conc. PCi/l

0000000000000

AUS. (PCI/1) Total Count

Elapsed Time (min.)

I/D _____

START DATE

2/20/18

START TIME

Kitchen 9:16

OPERATOR David Hollar

SERIAL NO.- CRM5106160

C/F (CPM/pCi/1) .380 BKG (pCi/1) .5 Hr Conc. / L RH B/P des pCi∕I B % "Hø F .9 / 14 28.9 62 .5 19 28.7 58 .3 23 28.7 59 .7 22 28.7 59 .5 17 28.9 60 .5 18 28.9 60 .2 14 29.0 61 .0 12 29.0 61 .0 14 29.0 61 .1 12 29.2 61 .5 13 29.0 60 .1 19 29.2 59 .3 12 29.2 59 .3 12 29.2 59 .1 12 29.2 58 .3 12 29.2 58 .9 / 14 28.9 62 3 .3 .7 .5 .5 .2 .0 .0 9 .0 10 11 12 13 14 15 16 12 29.2 58 .3 17 . t 13 12 29.2 56 12 29.2 58 12 29.3 58 11 29.3 58 11 29.2 51 .0 19 . 1 20 20 .1 21 .5 22 .2 23 .2 24 .2 25 .4 26 .8 27 .2 26 .5 29 .6
 22
 .2
 18 29.0
 47

 23
 .2
 15 29.2
 53

 24
 .2
 13 29.2
 55

 25
 .4
 14 29.2
 55

 26
 .8
 17 29.3
 57

 27
 .2
 20 29.5
 59

 28
 .5
 13 29.3
 58

 29
 .6
 15 29.3
 59

 30
 .9
 14 29.3
 59

 31
 .8
 15 29.3
 59
 18 29.0 47

32	.9	15 29.3	59
33	1.6	15 29.3	59
34	1.5_	13 29.3	59
35	. 9	8 29.5	61
36	.9	11 29.3	80
37	1.2	12 29.3	59
38	1.0	11 29.3	60
39	.7	11 29.3	59
40	1.2	12 29.3	59
41	1.2	12 29.3	58
42	1.2	12 29.3	58
43	1.7	12 29.3	58
44	1.2	12 29.3	58
45	1.5	12 29.3	58
46	1.9	11 29.3	58
47	2.3	11 29.2	57
48	1.6	13 29.2	56
49	1.4	14 29.2	56

Elapsed Time (min.) 2940
Total Count 1383
Avg. (pCi/l) .7

IND Jackson School Room 127

START DATE * 2/13/18 START TIME OPERATOR Monty Schmitt SERIAL NO.- CRM5106160 C/F (CPM/pCi/l) BKG (pCi/l) Hr Conc. / L RH B/P des pCi/l B % "He F 1.8 / 8 29.5 66
1.1 7 25.5 69
1.7 9 29.6 70
1.3 8 29.5 70
1.2 8 29.5 71
1.1 10 29.5 72
.8 10 29.3 72
1.2 8 29.3 71 2 3 4 5 6 7 3 1.2 8 29.3 8 29.3 7 1.4 70 10 3.0 8 29.3 70 3.8 3.7 5.6 6.8 9.6 8 29.2 1.2 8 29.2 69 8 29.0 69 8 29.0 69 8 29.0 69 8 29.0 69 8 29.0 69 11 3.8 8 29.2 59 12 13 14 15 11.2 17 18 19 20 9 29.0 21 16.5 13.5 8 29.0 23 8 29.0 69 11.1 24 5.8 8 29.0 69

3.2

9 29.0 69

26	2.3	1 1	29.0	70
27	1.4	11	29.0	70
28	1.3	9	29.0	70
29	.7	11	29.0	
30	1.0	12	28.9	70
31	1.3	11	28.9	
32	1.4	11	28.7	
33	2.0	11	28.7	
34	2.8	11	28.7	
35	3.8	11	28.7	69
96	4.4	11	28.7	
37	6.5	11	28.7	
38	8.2	12	28.7	
39	9.3	12	28.7	69
40	8.3	12	28.7	
41	8.2	12	28.7	69
42	11.0	12	28.7	89
43	11.7	12	28.7	69
44	10.5	12	28.7	69
45	11.9	12	28.7	69
46	11.7	12	28.9	69
47	7.3	12	28.9	69

Elapsed Time (min.) 2820 Total Count 7209 Ava. (pCi/l) 6.2

Appendix B

Maps









